

Commissioner for Patents
Page 3

Serial No.: 09/704,291

AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. Cancelled.
2. (Currently Amended) The method as claimed in claim 1-3 wherein the step of querying is performed by ~~the a~~ first edge router in the network.
3. (Currently Amended) A method of establishing explicit constrained edge-to-edge paths in a one of an Internet Protocol (IP), MPLS and Optical network that uses a modified open shortest path first (OSPF) routing protocol for constraint route distribution and path computation, comprising steps of:
provisioning at least one OSPF router in the network that supports constraint path setup with traffic engineering route exchange router (TE-X) functionality;
~~The method as claimed in claim 1 wherein the step of sending is performed by sending the TE LSAs~~ sending traffic engineering link state advertisement (TE-LSA) messages directly via unicast from the OSPF routers to only the a nearest one of the at least one TE-X, without flooding the TE-LSAs to other routers in the network, to permit each of the at least one TE-X to maintain a traffic engineering link-state database (TE-LSDB);
and
querying the nearest one of the at least one TE-X to obtain an explicit edge-to-edge path satisfying specified traffic engineering (TE) constraints.
4. (Currently Amended) The method as claimed in claim 1-3 further comprising a step of discovering the nearest one of the at least one TE-X via normal OSPF Router Link-State Advertisement messages.

Commissioner for Patents
Page 4

Serial No.: 09/704,291

5. (Original) The method as claimed in claim 4 further comprising a step of compiling and storing a list of all TE-Xs in a routing area and using the list to select a nearest TE-X based on a route cost factor associated with a shortest path route to respective TE-Xs in the list.
6. (Currently Amended) A method as claimed in claim ~~4~~3 further comprising a step of discovering peer TE-Xs in the network by learning at each TE-X of other TE-Xs using normal OSPF Router Link-State Advertisement messages (Router LSAs), and storing a list of other TE-Xs discovered in the network.
7. (Original) A method as claimed in claim 6 further comprising a step of sending one of a Hello and Keep-Alive message directly via unicast to each other TE-X discovered in the network.
8. (Currently Amended) The method as claimed in claim 7 further comprising a step of sending traffic engineering link states from each of the at least one TE-X to each other TE-X discovered in the network using a bi-directional communications connection set up with each other TE-X, in order to synchronize the TE-LSDBs.
9. (Currently Amended) The method as claimed in claim ~~4~~3 wherein each of the at least one TE-X advertises its capability as a TE-X using a TE-bit in an Options field of Router Link-State Advertisement (Router LSA) messages.
10. (Currently Amended) The method as claimed in claim ~~4~~3 further comprising a step of sending resources reserved (RR) TE-LSAs from the TE-X directly to peer TE-Xs in the network using a bi-directional communications connection set up with each peer TE-X to advise the peer TE-Xs of resources reserved when an explicit constrained path is established.

Commissioner for Patents
Page 5

Serial No.: 09/704,291

11. (Currently Amended) The method as claimed in claim 10 further comprising a step of sending a release explicit route message from an OSPF router that requested an explicit constrained path directly via unicast to the nearest TE-X, after the explicit constrained path is released, to permit the TE-X to flush RR TE LSAs related to the explicit constrained path that was released.
12. (Currently Amended) The method as claimed in claim 11 further comprising a step of sending resource reserved (RR) TE-LSAs from the TE-X to peer TE-Xs using a bi-directional communications connection set up with each peer TE-X in the network to permit the peer TE-Xs to flush the RR TE-LSAs related to the explicit constrained path that was released.
13. (Currently Amended) The method as claimed in claim 1-3 wherein the TE-LSAs include type, length, value (TLV) fields to define router addresses and link states.
14. (Original) The method as claimed in claim 13 wherein the TE-LSAs further include sub-TLV fields.
15. (Original) The method as claimed in claim 14 wherein the sub-TLV is a VPN sub-TLV used to indicate to other nodes in the network the VPN Identifier (VPN ID) that is associated with a router.
16. (Original) The method as claimed in claim 14 wherein the sub-TLV is a Replicating Capable sub-TLV used to indicate to other nodes that a router is capable of replicating data to more than one end point.

Commissioner for Patents
Page 6

Serial No.: 09/704,291

17. **(Currently Amended)** A traffic engineering route exchange router (TE-X) in a network that uses an open shortest path first (OSPF) routing protocol, comprising:
- a) a traffic engineering link-state data base (TE-LSDB) compiled using traffic engineering link-state advertisement (TE-LSA) messages received directly via unicast from OSPF routers in the network, each TE-X in the network receiving the TE-LSAs only from OSPF routers that have determined that the TE-X is a nearest one of the TE-Xs in the network; and
 - b) a messaging system for exchanging TE-LSA messages with peer TE-Xs in the network using a bi-directional communications connection set up with each peer TE-X.
18. **(Original)** The TE-X as claimed in claim 17 wherein the TE-X is an area border router (ABR).
19. **(Currently Amended)** The TE-X as claimed in claim 18 wherein the ABR exchanges summary TE-LSAs with peer TE-Xs in other routing areas to provide information respecting paths across ~~another the other routing area~~areas, and available resources associated with the paths.
20. **(Original)** The TE-X as claimed in claim 17 wherein on initialization the TE-X advertises its presence in the network using router link-state advertisement (Router LSA) messages.
21. **(Currently Amended)** The TE-X as claimed in claim 17 wherein a TE-bit is set in the Router LSA messages to advertise ~~to other routers in the network that the~~ TE-X has traffic engineering route exchange capability.
22. **(Original)** The TE-X as claimed in claim 17 wherein the TE-X discovers peer TE-Xs in the network.

Commissioner for Patents
Page 7

Serial No.: 09/704,291

23. (Original) The TE-X as claimed in claim 22 wherein the TE-X discovers peer TE-Xs in the network by exchanging normal OSPF routing information with other routers in the network and creating adjacencies with neighbors in the network.
24. (Original) The TE-X as claimed in claim 23 wherein the TE-X further derives and stores a list of peer TE-Xs in the network using a downloaded domain link-state database.
25. (Currently Amended) The TE-X as claimed in claim 24 wherein the TE-X further sends one of Hello and Keep-Alive messages directly via unicast to the other TE-Xs in the list, in order to discover a designated TE-X and a backup designated TE-X in the network.
26. (Original) A TE-X as claimed in claim 25 wherein the TE-X exchanges TE-LSA messages with the designated TE-X after peering with the designated TE-X, to obtain all current TE-LSAs for the network, and stores the TE-LSAs in the TE-LSDB.
27. (Original) A TE-X as claimed in claim 26 wherein the TE-X flushes from the TE-LSDB obsolete TE-LSAs when more current TE-LSAs are received from an OSPF router in the network, which originated the TE-LSA.
28. (Original) A TE-X as claimed in claim 17 wherein the TE-X:
- a) accepts queries from a first OSPF edge router for an explicit route between the first OSPF edge router and a second OSPF edge router in the network;
 - b) computes the explicit route using information stored in the TE-LSDB; and
 - c) sends information relating to the explicit route to the first OSPF edge router.

Commissioner for Patents
Page 8

Serial No.: 09/704,291

29. (Currently Amended) A TE-X as claimed in claim 27 wherein the TE-X updates the TE-LSDB when the information respecting the explicit route is sent to the first OSPF edge router.
30. (Currently Amended) A method of reducing traffic engineering messaging loads in an OSPF network, comprising steps of:
- a) configuring at least one OSPF router in the OSPF network as a traffic engineering route exchange router (TE-X);
 - b) ~~enabling-provisioning~~ the at least one TE-X to advertise to other OSPF routers in the network ~~to permit the other OSPF routers to distribute traffic engineering link state advertisement (TE-LSA) messages to at least one TE-X; and~~
 - e) ~~enabling-provisioning~~ the other OSPF routers in the network to send the traffic engineering link state advertisement (TE-LSA) messages directly via unicast to only a nearest one of the at least one TE-X, and to query only the nearest one of the at least one TE-X for an explicit route to an edge router in the network.
31. (Currently Amended) The method as claimed in claim 30 further comprising a step of enabling the at least one TE-X to build a traffic engineering link-state database (TE-LSDB) using the ~~at least one TE-LSA messages sent directly via unicast from the OSPF routers in the network,~~ and further enabling the TE-X to use the TE-LSDB for computing the explicit route.
32. (Currently Amended) The method as claimed in claim 31 further comprising a step of enabling the at least one TE-X to send copies of the TE-LSA messages directly using a bi-directional communications connection set up with each ~~to peer TE-Xs~~ TE-X in the OSPF network, and to receive TE LSA messages directly using a bi-directional communications connection set up with each ~~from peer TE-Xs~~ TE-X in the OSPF network.

Commissioner for Patents
Page 9

Serial No.: 09/704,291

33. (Original) The method as claimed in claim 32 further comprising a step of enabling the at least one TE-X to flush outdated TE-LSAs from the TE-LSDB when a more current TE-LSA is received.
34. (Currently Amended) The method as claimed in claim 30 further comprising steps of:
- a) enabling the other OSPF routers in the network to compile a list of the at least one TE-X in the network using network routing information; and
 - b) to select the nearest TE-X based on a least cost route of respective routes to respective ones of the at least one TE-X.
35. (Original) The method as claimed in claim 34 further comprising a step of enabling the other OSPF routers in the network to select a nearest TE-X by sending a probe message to the at least one TE-X in an order of least cost route until a one of the at least one TE-X acknowledges the probe message, thereby accepting to serve as nearest TE-X to the other OSPF router sending the probe message.
36. (Currently Amended) The method as claimed in claim 35 further comprising a step of enabling the other OSPF routers in the network to select a backup TE-X by sending a probe message to TE-Xs remaining after selecting the nearest TE-X in an order of least cost route until a one of the remaining TE-Xs acknowledges the probe message, thereby accepting to serve as backup TE-X to the other OSPF router sending the probe message.
37. (Original) The method as claimed in claim 30 further comprising a step of enabling the at least one TE-X to advertise to other OSPF routers in the network using a TE-bit in an Option field of an OSPF Router LSA message.

Commissioner for Patents
Page 10

Serial No.: 09/704,291

38. (Currently Amended) A data network that uses an open shortest path first (OSPF) routing protocol, comprising:
- a) a plurality of OSPF routers, at least one of the OSPF routers being adapted provisioned to function as a traffic engineering route exchange router (TE X); and
 - b) a remainder of the routers being adapted ~~provisioned~~ to send traffic engineering link-state advertisement (TE-LSA) messages directly via unicast to only a nearest one of the at least one TE-X, to enable the nearest one TE-X to maintain a traffic engineering link-state database (TE-LSDB) for computing explicit routes between edge routers in the data network.
39. (Currently amended) A data network as claimed in claim 38 wherein the at ~~least nearest one~~ TE-X is further adapted to send a copy of each TE-LSA received from the other OSPF routers in the data network directly using a bi-directional communications connection set up with ~~to~~ each peer TE-X in the data network.
40. (Currently amended) A data network as claimed in claim 39 wherein the other routers in the data network query the nearest one of the at least one TE-X to obtain an explicit route to another router in the data network.
41. (Currently Amended) A data network as claimed in claim 38 wherein the at ~~least one nearest~~ TE-X is an area border router (ABR) in a routing area of the data network.
42. (Currently Amended) A data network as claimed in claim 38 wherein the at ~~least one nearest~~ TE-X is an autonomous system border router (ASBR) in an autonomous system of the data network.

Commissioner for Patents
Page 11

Serial No.: 09/704,291

43. (Currently Amended) A data network as claimed in claim 41 wherein the ~~ABR-ASBR~~ peers with TE-Xs in other routing areas of the data network to which the ~~ABR-ASBR~~ is connected.
44. (Original) A data network as claimed in claim 42 wherein the ASBR peers with TE-Xs in other autonomous systems and other routing areas of the data network to which the ASBR is connected.
45. (Currently Amended) A data network as claimed in claim ~~29-38~~ wherein the data network is one of an Internet Protocol (IP), Multi-protocol Label Switched (MPLS), and Optical network.